


$\phi 29\text{-}1/4"$ [743MM] C.C.
(TYPICAL)

NON-PENETRATING
PICKHOLE
(SEE DETAIL)

NOTES:

- 1.) MATERIAL SHALL BE GRAY CAST IRON CONFORMING TO A.S.T.M. A48 (LATEST REVISION) CLASS 30B. SECTION THICKNESS AT ANY POINT SHALL BE A MINIMUM OF 1/2".
- 2.) UNITS DESIGNED HEAVY DUTY FOR A.A.S.H.T.O. HS20-44 WHEEL LOADS.
- 3.) EACH FRAME AND COVER SHALL HAVE MACHINED HORIZONTAL BEARING SURFACES.
- 4.) DIMENSIONS ARE APPLIED USING SOFT CONVERSION. ALL DIMENSIONS IN BRACKETS ARE MILLIMETERS.



NON-PENETRATING
PICKHOLE
DETAIL

#1007AC FRAME AND COVER
"GREASE" - CAST IRON

DRAWING # 032408-DA

FILE # 1007475C-1007MOD7PC

Drawn By: ARO DATE: 05/02/00 Revised By: DA Revised: 03-24-08



SYRACUSE CASTINGS SALES CORP.
P.O. Box 1821 / 6177 South Bay Rd.
Cicero, N.Y. 13039
315-699-2601 Fax # 315-699-2982
www.syracastl.com

SECTION A - A